



2X ULTRA COVER ENAMEL SPRAYS

DESCRIPTION AND USES

Rust-Oleum® 2X Ultra Cover Enamel Sprays are designed to provide twice the coverage on wood, metal, plastic, wicker and more. These sprays cover surfaces with less spray passes, allowing projects to be completed faster and easier. 2X Ultra Cover Enamel Sprays feature an any angle spray that allows you to spray in any direction, even upside down. A comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying. Not for use on galvanized metal.

TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
276262	Gloss Apple Red
276264	Gloss Berry Pink
276265	Gloss Colonial Red
276266	Gloss Deep Blue
276267	Gloss Grape
276268	Gloss Key Lime
276310	Gloss Meadow Green
276311	Gloss Real Orange
276312	Gloss Seaside
276313	Gloss Sun Yellow
276314	Gloss White
276315	Gloss Black
349311	Gloss Pastel Peppermint
349312	Gloss Plush Pink
350198	Gloss Hunter Green
276312	Gloss Seaside
276351	Gloss Dark Grey
286841	Gloss Ocean Mist
28643	Gloss Winter Grey
349309	Satin Blue Diamond
276316	Satin Blossom White
276317	Satin Canyon Black
276318	Satin Espresso
276319	Satin Heirloom White
276320	Satin Lagoon
349310	Satin Modern Mauve
286844	Satin Poppy Red
276352	Satin Dark Walnut
276353	Satin Granite
276354	Satin Ivory Silk
286828	Satin Eden
276323	Flat Black
276324	Flat White

PRODUCT APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. All surfaces must be dry at time of application. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

PRIMING

Use of Rust-Oleum® 2X Ultra Cover Primer will optimize adhesion and hiding and is recommended for bare wood and metal.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-40 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT TIMES

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply the clear coat in 2-3 light coats a few minutes apart. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with mineral turps. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not stick pin or any object into the stem.

	TECHNICAL DATA	ROC-36
	2X ULTRA COVER ENAMEL SPRAYS	

PHYSICAL PROPERTIES

		2X ULTRA COVER ENAMEL SPRAYS
Resin Type		Acrylic Modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, Ethyl Benzene, Xylene
MIR		Max 0.95
Fill Weight		340 grams
Recommended Dry Film Thickness (DFT) per Coat		25-50µ
Practical Coverage at Recommended DFT (assume 15% material loss)		4.5 m ² /can
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 48 hours
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.